

665 SCOTCH™ LINERLESS DOUBLE COATED TAPE

DESCRIPTION :

A transparent plastic film tape with synthetic acrylic on both sides.

This double coated tape has **no liner**.

CHARACTERISTICS :

Backing	: Acetate of cellulose
Adhesive	: 2 different acrylic adhesives
Adhesion to steel	: Interior side: 2,7 N/cm Exterior side: 2,5 N/cm
Tensile strength	: 2,8 daN/cm
Total tape thickness	: 0,080 mm



PRODUCT FORMS :

Roll mounted on one inch core and/or 3 inches core diameter.

USES :

- . Splicing /joining of papers, foils and films
- . Mounting of posters to outside windows with sunlight exposures
- . Attaching novelties greeting cards
- . Positioning of textiles articles samples in display packages

PRODUCT BENEFITS :

- . **Firm permanent adhesive coated on both sides: it sticks and holds instantly**
- . **Extremely long aging resistance: no dry out or stain of the adhesive**
- . **Thin tape having an excellent cuttability**
- . **Acetate of cellulose tape is chlorine free**
- . **Linerless: easy to use, no need of a special dispenser. No waste**
- . **Moisture resistant**

TECHNICAL NOTE :

Application below 10°C is not recommended because the adhesive becomes too firm to adhere.